



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			
Built Date	2001	Length Over Strikers	77'-10"	Truck Type	ASF SS Ride Master	Brake Control Valve	NYAB DB-60SL
Car Builder	Trinity Ind	Length Over Pulling Faces*	82'-2"	Bols. Patt./ AAR Code	B9A-YY4N-FX, Gr B+	Portioning Valves	DB-10 / DB-20
Builder Lot No.	2829	Truck Centers	52'-0"	Side Frame/AAR Code	F9A-11EN-UA, Gr B+	Brake Cylinder	10" X 12" ABU
AFE Number		Inside Length	72'-2"	Truck Spring Group	7 D-5 O, 7 D-5 I, 2 D-6A II	Slack Adjuster	Universal 2300-DJ
AAR Mech. Design.	RP	I W (Corrugations)	9'-2"	Snubbing Type	ASF SS Ride Master	Brake Beam	Triax-Jackson Model 2531
AAR Car Code	R660	I W (Side Sheets)	9'-3"	Snubber Spring Group	ASF 5062 O, ASF 5063 I	Brake Beam Wear Pl	Zeftek ZT-1696-NH
GST Code	R8N	Inside Height	11'-11"	Column Wear Plate	ASF 98-1-10232	Brake Shoes	Wabtec Cobra 2"
Clearance Plate	Plate F	Ext Width (@ 3'- 7")	10'-5"	Pedestal Roof Liners	Transdyne A05048	Handbrake	Klasing 1700-1
C.G. - Empty	65"	Extreme Height	17'-0"	Wheels	36", H-36, Class C	Floor (Sub)	Creative Pultrusions
C.G. -Loaded*	98"	Volume (@ 9'-2")	7883 cu. ft.	Roller Bearing	Timken 6 1/2X9, AP-2	Floor (Main)	Alum. Plate
Min Curve-Cpl'd	350 ft.	Volume (@ 9'-3")	7954 cu. ft.	Pedestal Adapter	6 1/2" X 9"	Doors (Single Plug)	YSD 12'-0" X 11'-3 1/2"
Min Curve-Uncpl'd	180 ft.	Gross Rail Load	286000	Truck Side Bearing	A. Stucki 688-BR	Lading Anchors	Ireco Kit 7800, 80/Car
Brake Ratio-Empty	26.88%	Light Weight (full fuel tank)	105000	Horiz Center Plate Liner	Mn Stl	Roof Assy	Molded Fibreglass
Brake Ratio-Loaded	9.78%	Load Limit	181000	Vertical Wear Ring	1/4" X 2" Stainless Steel	Load Dividers	N/A
Brake Ratio-H.B.	10.35%	Floor Rating	50K	Coupler/Knuckle*	M&T EF603CE / E50BE	Lining (Side)	Bulitex
		Door Opening Width	12'-0"	Draft Sill / Striker Assy.	Trinity Fabricated	Lining (End)	Bulitex
		Door Opening Height	11'-3 1/2"	Front Draft Lug		Lining (Ceiling)	FRP Integral W/Roof
		Floor Height (Light Car)	4'-1 9/16"	Rear Draft Lug	Trinity Fabricated	Plenum (Ceiling)	Bulitex Panel
		UA	211	Center Plate	ASF 15 7/8"D-Low Profile	Insulation	2.2 lb Density
FORMER REPORTING MARKS				Coupler Carrier Wear Pl	Trinity Mn	Refrigeration (Carrier)	Ultima 2-NDX 93D-M
New				Uncoupling Device	Stanrail No. 10420	Fuel Tank	NorthSide Ind 325 Gal
NOTES AND EXCEPTIONS:				Draft Gear	N/A	Side Rub Rails	N/A
* 98" C.G. is with lading restricted to 11'-9" above the floor.				Cushioning	ASF/Keystone, E-13-2	Satellite System	StarTrak
* 82'-2" length over pulling faces is if equipped with 13/2 cushioning unit				Yoke	ASF/Keystone, YF-15-J	Bulkhead Fixed	Creative Pultrusions
BNSF 793200-793699 Equipped with or for Ireco Wall Lading Anchors						Paint	Valspar Ext.
BNSF 793000-793074 Equipped with Buffalo BB 524 L&R Beams						Decals	Trinity Avery Dennison
BNSF 793075-793104 Equipped with Triax Model 2520 Beams							
Replacement coupler to be EF-60WBE or EF-603CE – SAP #1009048785							
Clarified dimensions - JWM 6/3/14							